

Silicone NFC Smart Ring-spec sheet




This NFC smart ring is made of eco-friendly silicone material, waterproof, and durable. Compared with Ceramic NFC rings, silicone NFC Smart Ring is much cheaper. And it is very suitable for access control management applications that required waterproof. For example, swimming pools, water parks, gyms, sports clubs, etc.

The silicone NFC ring is easy to use. Wear it on your finger and $% \left(1\right) =\left(1\right) \left(1\right) +\left(1\right) \left(1\right) \left(1\right) +\left(1\right) \left(1\right)$ you'll never have to worry about forgetting your access card. And it also can be used as a metro card, membership card, and

| Parameters | | | | | | | | |
|------------|---|------------------------|--|------------------------|-----------|--|--|--|
| Item | NFC Smart Ring | Color | Black, white | Working Temperature | -20~+70°C | | | |
| Material | Silicone | Craft | silkscreen logo/Laser serial number UID print etc | Data Retention Time | 10 years | | | |
| Chip | TK4100, Ntag213, Ntag215 Ntag216, etc. | Write Endurance | 100000 times | Туре | NFC | | | |
| Size | ф16.5 mm, ф17.3 mm, ф18.2 mm, ф1 | 8.9 mm, ф19.8 mm, ф20. | | | | | | |

Dimensional Diagram




| Size or Customized | | | | | | | | |
|--------------------|--------|--------|--------|--------|--------|--------|--------|--|
| US | 6 | 7 | 8 | 9 | 10 | 11 | 12 | |
| Circumference | 5.3cm | 5.6cm | 5.9cm | 6.2cm | 6.5cm | 6.8cm | 7.1cm | |
| Diameter | 16.5mm | 17.3mm | [8.2mm | 18.9mm | 19.8mm | 20.7mm | 21.3mm | |

APPLICATIONS

- Member management
- Pet/lost tracking
- Gaming and identity

- Access control Management
- Swimming pool
- Hotel management
- Payment tracking
- Event ticketing
- Transportation card

O JingYuan Mansion FL 16, LongGang, Shenzhen, China 518112









Available chips

HF 13.56 MHz Chips

| Chip Name | Protocol | Capacity | Frequency | |
|-----------------------|-----------|-----------|-----------|--|
| Ntag213 | ISO14443A | 180 byte | 13.56 MHz | |
| Ntag215 | ISO14443A | 540 byte | 13.56 MHz | |
| Ntag216 | ISO14443A | 924 byte | 13.56 MHz | |
| MIFARE Classic 1K | ISO14443A | 1 KB | 13.56 MHz | |
| MIFARE Classic 4K | ISO14443A | 4 KB | 13.56 MHz | |
| MIFARE Ultralight EV1 | ISO14443A | 80 byte | 13.56 MHz | |
| MIFARE Ultralight C | ISO14443A | 192 byte | 13.56 MHz | |
| ICODE SLIX | ISO15693 | 1024 bits | 13.56 MHz | |

Feature

- Eco-Friendly, recycled, washable, and durable
- Customized service: Various styles, crafts, colors that you can choose
- IP68 grade waterproof and dustproof, durability, and anti-fall
- ▶ Built-in ultra-sensitive NFC chip, no need to charge, ready to use
- Available in all sizes: 6-12 (American standard) or customize
- Multi-function: access control, identification, payment, etc.

